



Technical data

Insulating cable tray **66** in **U23X**

Description

Use

- For support, protection and conduction of cables.
- Insulating material.
- Length: 3m.
- Colour: RAL 7035 Grey.

Installation

- Safe, easy and quick mounting. No burrs when cutting.

Product characteristics

- Cable tray system for outdoor/indoor installations. Suitable for humid, saline and chemical environments: U23X. ⁽¹⁾
- Insulating supports for outdoor/indoor installations. Suitable for humid, saline and chemical environments: U23X. ⁽¹⁾
- Metallic supports for outdoor/indoor installations. Suitable for humid, saline and chemical environments: Stainless steel AISI 304. ⁽¹⁾
- Metallic supports for outdoor/indoor installations. Suitable for humid, saline and chemical environments: Galvanized steel with epoxy coating. ⁽¹⁾
- Metallic supports for dry indoor installations: Sendzimir galvanized steel.
- Silicone contents: Without silicone (<0,01%).
- RoHS Directive compliance: Compliant .

Technical data

Insulating cable tray **66** in **U23X**

Quality Marks ⁽²⁾



(3)

EN 61537: 2007
Licence n°: 030/001911



(3)

EN 61537: 2007
Licence n°: 670639



(3)

EN 61537: 2007
Licence n°: 40011889



ANSI / UL 568: 2009 -
CAN/CSA C22.2 No. 126.2-
02
Licence n°: E335136



POCC ES.AF
19.H03293

Approvals ⁽²⁾



Type approval Certificate n°
05116/G3 BV



FZ 123-FZ
C-ES.N523.B00076

Characteristics

EN 61537:2007 / IEC 61537:2006 (INTERNATIONAL CABLE TRAY STANDARD)

Min./max. Service, transport, storage, installation and use temperature	-20° C up to +60° C.
Protection against mechanical damage	20 J at -20°C (except 60x100: 10 J and 60x75: 5 J).
Electrical characteristics	<ul style="list-style-type: none"> ■ Insulating Cable tray and support system (except metallic supports) ■ Without electrical continuity. Non-conductive system.
Resistance to flame propagation s/ EN 60695-11-2:2003 ⁽⁴⁾	Non flame propagating system.
Coating	Without coating (except metallic supports with metallic coating and metallic supports with organic coating).
% perforation in the base area	Class B (between 2% and 15%) for perforated cable tray. Class A (between 0% and 2%) for non perforated cable tray.

Technical data

Insulating cable tray **66** in **U23X**

Characteristics

EN 61537:2007 / IEC 61537:2006 (INTERNATIONAL CABLE TRAY STANDARD)

Safe Working Load (SWL) acc. Test Type I ⁽⁵⁾	<ul style="list-style-type: none"> ▪ 60x75 mm : 7,9 Kg/m ▪ 60x100 mm. : 10,8 Kg/m ▪ 60x150 mm. : 16,6 Kg/m ▪ 60x200 mm. : 22,5 Kg/m ▪ 60x300 mm. : 33,7 Kg/m ▪ 60x400 mm. : 45,6 Kg/m ▪ 100x200 mm. : 37,6 Kg/m ▪ 100x300 mm. : 57,3 Kg/m ▪ 100x400 mm. : 77,2 Kg/m ▪ 100x500 mm. : 96,6 Kg/m ▪ 100x600 mm. : 116,5 Kg/m
Glow-wire test acc./ IEC 60695-2-11:2001 ⁽⁴⁾	Severity degree 960°C.
Resistance against humid and saline corrosion	Inherently resistant to corrosion. Test is not necessary.

DIN 8061 AND ISO/TR 10358

Performance against chemical ambiances	Chemical resistance against different substances defined by the standard depending on the concentration and temperature.
--	--

ANSI/UL 568:2009 AND CAN/CSA C22.2 NO. 126.2-02

Outdoor performance	Good performance with exposure to the UVs and to the elements. Product Certified UL LISTED as "Suitable for outdoor".
---------------------	---

EN 50085-2-1:2006 + A1:2011

Material	Non metallic.
Minimum storage and transport temperature	-45°C
Minimum installation and application temperature	-25°C
Maximum application temperature	+60°C
Resistance against mechanical impacts during mounting and use	Cable tray with cover: 20 J at -25°C
Resistance to flame propagation acc./ IEC 60695-11-2:2003 ⁽⁶⁾	Non-flame propagation.
Electrical continuity characteristic	Without electrical continuity characteristic.

Technical data

Insulating cable tray **66** in **U23X**

Characteristics

EN 50085-2-1:2006 + A1:2011

Electrical insulating characteristic	With electrical insulating characteristic.
Protection degree assured by the enclosure acc./ IEC 60529:1989 (6)	<ul style="list-style-type: none"> ■ IP3X. Continuous cable tray with cover. ■ IP2X. Perforated cable tray with cover.
Retention of the system access cover	Cover removable only with the aid of a tool.
Electrically protective separation	With and without internal protective separation.
Intended installation positions	Surface mounted on the wall.
Prevention of contact with liquids	Not declared.
Type	Type 2. (distribution)
Rated Voltage ⁽⁷⁾	750 V.
Protection against mechanical damage acc./ IEC 62262:2002 ⁽⁸⁾ (6)	Cable tray with cover: Degree IK10.

EN 60695-2-11:2001

Glow-wire test	Severity degree: 960°C.
----------------	-------------------------

Constructive and Functional characteristics

- Installation instructions: Cable trays and accessories must be installed according to the manufacturer`s instructions delivered inside the cable tray packaging.
- Profile type: Cable trays and covers are made of solid walls and by extrusion.
- Junctions: The junction`s thickness is equal or higher than the one of the joined lengths of tray and has longitudinal holes to absorb expansion.
- Insulation: The cable tray is insulating and does not require earthing.
- Supports: Supports must comply with IEC 61537:2006 and shall resist at least the maximum loads of the carried cable trays.
- Packaging: The product must be properly packed and clearly identified.

Compulsory regulations

CONFORMITY WITH THE DEMANDS OF EUROPEAN DIRECTIVE 2014/35/EC

CE Marking ⁽³⁾	Conformity with standard EN 61537:2007.
---------------------------	---

Technical data

Insulating cable tray **66** in **U23X**

Characteristics of U23X raw material

- Base raw material: PVC.
- Silicone contents: <0,01%.
- Phtalate contents according to ASTM D2124-99:2004: <0,01%.
- Dielectric strength according to EN 60243-1:2013: 18±4 kV/mm.
- Reaction to fire according to UNE 201010:2015: Classification: M1.
- UL flammability tests on plastic materials according to ANSI/UL 94: 1990: Degree UL94: V0.
- L.O.I. Oxygen index according to EN ISO 4589:1999 + A1:2006: (Concentration %) = 52±5.
- Coefficient of linear expansion: 0,07 mm/°C m. ⁽⁹⁾
- UL Approval: UL File E317944 (only extrusion formula, grey and blue colour).

Characteristics of steel coated with epoxy resin raw material

- Base raw material: Stainless steel
- Coating: Epoxy/polyester resin
- Classification: Steels DD11 acc./EN 10111:2008 and DC01 acc./EN 10130:1999

Characteristics of stainless steel coated with epoxy resin raw material

- Base raw material: Steel.
- Coating: Highly corrosion resistant coating+ epoxy / Polyester resin
- Classification: EN 10088: 1.4301
AISI:AISI 304
NF A35-586:Z6CN 18-09
DIN 17440:1.4301(V2A)
BS:304,S31
EN ISO 3506 A2

Characteristics of sendzimir steel raw material

- Base raw material: Steel
- coating according to EN 10130:1998: Pre-galvanized steel Z275-MBO
- Classification acc./EN 10142: 2000: DX53D+Z275-MBO

Characteristics of PVC Plasticized raw material

- Base raw material: PVC plasticized
- UL flammability tests on plastic materials according to ANSI/UL 94: 1990: degree UL94 V0

Technical data

Insulating cable tray **66** in **U23X**

Notes

1. In outdoor installations or in aggressive chemical environments it is necessary to periodically check the installation.
2. Except for new part numbers, which are under process of obtaining quality marks and approvals.
www.unex.net/QM.pdf
3. The values indicated according to IEC 61537:2006 have been tested under its European implementation EN 61537:2007.
4. Tested according to standard prescriptions of EN 61537:2007 / IEC 61537:2006
5. BS EN 61537:2007 (IEC 61537:2006) Safe Working Load (SWL) Test conditions: • T = 40 °C span 1,5 m. • T = 60 °C span 1 m. • Longitudinal deflection lower than 1% and transverse lower than 5%. • Test Type I (the junction between two lengths can be placed at any point between two supports) • The system (cable tray and supports) must be able to support 1,7 times the admissible load without collapse.
6. Tested according to standard prescriptions of EN 50085-1
7. Test carried out considering the use of the cable tray with cover to provide additional insulation to an isolated conductor according to requirements of EN 50085-1 standard (Low Voltage Directive)
8. Mounted with Cover fixing Ref. 66845 or 66855. Without this device: Impact resistance 2J and Protection against mechanical damages Grade IK07.
9. All features marked are based on random tests of the material in the manufacture of our products. However, they only reflect the values accepted by the raw material manufacturers, which are provided only as information and guidance.

* All information contained herein is completely objective and is the result of a wide experience in satisfying our costumers` requirements . For more details, please visit our website.

** Unex aparellaje eléctrico, S.L. reserves the right to modify any characteristics of the products manufactured. This document is an uncontrolled copy and will not be updated if its content changes.

25/8/2016